



terrex™ fast a393



colors:

	frames	lenses
	black/black/ 00 6050	LST Bluelight silver + LST Bright (antifog)
	darkgrey/red/ 00 6051	LST Active silver + LST Bright (antifog)
	white met/lime/ 00 6052	SPACE + LST Bright (antifog)
	magenta/pink/ 00 6053	LST Bluelight silver + LST Bright (antifog)

lens technology:



package consists of:



RXready:



terrex™ fast

a393

adapter parameters:

adapter model	lens horizontal	RX range	cylinder
a534	54 mm	-2.75/+1.50 dpt	-2.00/+2.00 dpt



Adapter Glazing a534

	mm	54 x 34 (1568 mm ²)
	mm	59
	mm	24
	°	25

performance insert:



model	lens horizontal	RX range	cylinder
a731	39 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



rimless insert chassis
model

a515



model

a516



terrex™ swift a394



colors:

	frames	lenses
	black/black/ 00 6050	grey
	chocolate/black/ 00 6051	LST Contrast silver
	iceblue/brown/ 00 6052	LST Contrast silver
	silver/black/ 00 6053	LST Active silver

lens technology:



package consists of:



RXready:



terrex™ swift a394

adapter parameters:

advanced edging parameters:

performance insert:



model	lens horizontal	RX range	cylinder
a731	39 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



rimless insert chassis
model

a515



model



a516



evil eye L a266



colors:

	frames	lenses
	black/ 00 6065	LST Active (antifog)
	white/ 00 6066	LST Active silver light

lens technology:



package consists of:



RXready:



evil eye L

a266

adapter parameters:

advanced edging parameters:

performance insert:



model	lens horizontal	RX range	cylinder
a727	39 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



model	lens horizontal	RX range	cylinder
a731	39 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



rimless insert chassis
model
a516



evil eye pro L a126



colors:



frames

race silver/black/
00 6077

lenses

LST Active silver +
LST Bright (antifog)



race transparent/
orange/
00 6080

LST Active silver +
LST Bright (antifog)



race white/black/
00 6081

LST Active silver +
LST Bright (antifog)



matt black/
chrome/
00 6082

LST Active (antifog)
+ LST Bright
(antifog)

lens technology:



package consists of:



RXready:



evil eye pro L

a126

adapter parameters:

advanced edging parameters:

performance insert:



model	lens horizontal	RX range	cylinder
a727	39 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



model	lens horizontal	RX range	cylinder
a731	39 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



rimless insert chassis
model
a516



evil eye pro S a127



colors:

	frames	lenses
	race silver/black/ 00 6077	LST Active silver + LST Bright (antifog)
	race transparent/ orange/ 00 6080	LST Active silver + LST Bright (antifog)
	race white/black/ 00 6081	LST Active silver + LST Bright (antifog)
	matt black/ chrome/ 00 6082	LST Active (antifog) + LST Bright (antifog)

lens technology:



package consists of:



RXready:



evil eye pro S

a127

adapter parameters:

advanced edging parameters:

performance insert:



model	lens horizontal	RX range	cylinder
a731	39 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis

model

a516





evil eye halfrim pro L a167



colors:

	frames	lenses
	shiny black/green/ 00 6050	LST Active silver + LST Bright (antifog)
	shiny brown/ offwhite/ 00 6051	LST Active (antifog) + LST Bright (antifog)
	matte white/ caramel/ 00 6053	LST Active gold + LST Bright (antifog)
	matte black/grey/ 00 6054	LST Active silver + LST Bright (antifog)
	neonorange/ 00 6058	LST Active silver + LST Bright
	neonblue/ 00 6059	LST Active silver + LST Bright

lens technology:



package consists of:



RXready:





available to purchase without lenses for adapter use

evil eye halfrim pro L

a167

adapter parameters:

adapter model	eye size	B measurement	DBL	base curve
a530	59	39.6	20	8.50
	lens horizontal	Rx Range	cylinder	
	57 mm	-3.75/+ .50 dpt	-2.00/+2.00 dpt	
	model details			
	58-59	60-62	63-66	67-70
PLY/TRIVEX* S	-2.50/PL	-3.00/PL	-3.25/PL	-3.25/+ .25
PLY/TRIVEX* P	-1.25/PL	-1.75/PL	-1.75/PL	-2.00/PL
PLY S	-2.75/+ .25	-3.25/+ .25	-3.50/+ .50	-3.75/+ .50
TRIVEX S	-2.50/+ .25	-3.00/+ .25	-3.25/+ .25	-3.75/+ .25

PD [**S** – Single Vision | **P** – Progressive], *Parameters for Shamir Autograph II Attitude

Adapter Glazing a530



mm 57 x 38 (1729 mm²)



mm 62



mm 20



21° lens groove curve 8

performance insert:



model	lens horizontal	RX range	cylinder
a731	39 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



rimless insert chassis
model

a515



model

a516



evil eye halfrim pro S a168



colors:

	frames	lenses
	shiny black/green/ 00 6050	LST Active silver + LST Bright (antifog)
	shiny brown/ offwhite/ 00 6051	LST Active (antifog) + LST Bright (antifog)
	matte white/ caramel/ 00 6053	LST Active gold + LST Bright (antifog)
	matte black/grey/ 00 6054	LST Active silver + LST Bright (antifog)
	neonorange/ 00 6058	LST Active silver + LST Bright
	neonblue/ 00 6059	LST Active silver + LST Bright

lens technology:



package consists of:



RXready:



available to purchase without lenses for adapter use

evil eye halfrim pro S

a168

adapter parameters:

adapter model	eye size	B measurement	DBL	base curve
a531	53	36.1	20	8.50



lens horizontal	Rx Range	cylinder
51 mm	-5.00/+1.75 dpt	-2.00/+2.00 dpt

model details

	58-59	60-62	63-66	67-70
PLY*	S -4.00/+2.25	-4.00/+2.25	-4.25/+5.50	-4.50/+7.75
TRIVEX*	S -3.50/+2.25	-3.75/+5.50	-4.00/+7.75	-4.25/+10.00
PLY*	P -3.75/+2.25	-4.00/+2.25	-4.25/+5.50	-4.50/+5.50
TRIVEX*	P -3.00/+2.25	-3.25/+2.25	-3.50/+2.25	-3.75/+5.50
PLY	S -4.25/+1.25	-4.50/+1.25	-4.75/+1.50	-5.00/+1.75
TRIVEX	S -4.00/+7.75	-4.50/+1.00	-4.75/+1.00	-5.00/+1.25

PD (S - Single Vision | P - Progressive), *Parameters for Shamir Autograph II Attitude

Adapter Glazing a531		mm	51 x 35 (1416 mm ²)
		mm	55
		mm	21
		°	18° lens groove curve 8

performance insert:



model	lens horizontal	RX range	cylinder
a731	39 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis
model

a515

model

a516



evil eye halfrim L a402



colors:

	frames	lenses
	shiny black/red/ 00 6050	LST Active silver
	matte blue/ orange/ 00 6051	LST Contrast
	shiny white/ anthracite/ 00 6054	LST Active silver
	matte silver/ black/ 00 6057	LST Active silver

lens technology:



package consists of:



RXready:



available to purchase without lenses for adapter use

evil eye halfrim L

a402

adapter parameters:

adapter model	eye size	B measurement	DBL	base curve
a530	59	39.6	20	8.50



lens horizontal	Rx Range	cylinder
57 mm	-3.75/+ .50 dpt	-2.00/+2.00 dpt

model details

58-59	60-62	63-66	67-70
-------	-------	-------	-------

PLY/TRIVEX* **S** -2.50/PL -3.00/PL -3.25/PL -3.25/+ .25

PLY/TRIVEX* **P** -1.25/PL -1.75/PL -1.75/PL -2.00/PL

PLY **S** -2.75/+ .25 -3.25/+ .25 -3.50/+ .50 -3.75/+ .50

TRIVEX **S** -2.50/+ .25 -3.00/+ .25 -3.25/+ .25 -3.75/+ .25

PD (S - Single Vision | P - Progressive), *Parameters for Shamir Autograph II Attitude

Adapter Glazing a530



mm 57 x 38 (1729 mm²)



mm 62



mm 20



21° rx lens groove curve 8

performance insert:



model	lens horizontal	RX range	cylinder
a731	39 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



rimless insert chassis
model

a515



model

a516



evil eye halfrim S a403



colors:

	frames	lenses
	shiny black/red/ 00 6050	LST Active silver
	matte blue/ orange/ 00 6051	LST Contrast
	shiny white/ anthracite/ 00 6054	LST Active silver
	matte silver/ black/ 00 6057	LST Active silver

lens technology:



package consists of:




RXready:



available to purchase without lenses for adapter use

evil eye halfrim S a403

adapter parameters:

adapter model	eye size	B measurement	DBL	base curve
a531	53	36.1	20	8.50
	lens horizontal	Rx Range	cylinder	
	51 mm	-5.00/+1.75 dpt	-2.00/+2.00 dpt	
	model details			
	58-59	60-62	63-66	67-70
PLY*	S -4.00/+2.25	-4.00/+2.25	-4.25/+5.50	-4.50/+7.75
TRIVEX*	S -3.50/+2.25	-3.75/+5.50	-4.00/+7.75	-4.25/+10.00
PLY*	P -3.75/+2.25	-4.00/+2.25	-4.25/+5.50	-4.50/+5.50
TRIVEX*	P -3.00/+2.25	-3.25/+2.25	-3.50/+2.25	-3.75/+5.50
PLY	S -4.25/+1.25	-4.50/+1.25	-4.75/+1.50	-5.00/+1.75
TRIVEX	S -4.00/+7.75	-4.50/+1.00	-4.75/+1.00	-5.00/+1.25

PD (S – Single Vision | P – Progressive), *Parameters for Shamir Autograph II Attitude

Adapter Glazing a531



mm 51 x 33 (1367 mm²)



mm 55



mm 21



18° rx lens groove curve 8

performance insert:



model	lens horizontal	RX range	cylinder
a731	39 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis
model

a515

model

a516





adivista L a164



colors:

	frames	lenses
	shiny black/ 00 6051	LST Contrast
	matt copper/ 00 6051	LST Vario
	matt silver/ 00 6052	LST Contrast silver
	white/ 00 6054	LST Vario
	shiny red/ 00 6064	LST Active silver
	matt black/ 00 6071	LST Contrast gold
	shiny petrol/ 00 6072	LST Contrast silver
	phantom/ fresh lemon/ 00 6088	LST Contrast silver
	silvermet/ lime/ 00 6089	LST Active silver

lens technology:



package consists of:



RXready:







adivista L

a164

adapter parameters:

adapter model	lens horizontal	RX range	cylinder
a745	63 mm	-4.00/+2.00 dpt	-2.00/+2.00 dpt

Adapter Glazing a745

	mm	63 x 43 [2183 mm ²]
	mm	69
	mm	17
	°	28



advanced edging parameters:

model / name	eye size	B measurement	bridge size	base curve
a164 / adivista L	72	43	10	8

model details

	58-59	60-62	63-66	67-70
single	-2.75/+2.25	-2.75/+50	-2.75/+50	-2.75/+75
progressive	-1.00/+25	-1.50/+50	-1.75/+75	-1.75/+100

PD

performance insert:

model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



rimless insert chassis

model

a515





adivista S a165



colors:

frames

lenses



shiny black/
00 6050

LST Contrast



matt copper/
00 6051

LST Vario



matt silver/
00 6052

LST Contrast silver



white/
00 6054

LST Vario



shiny red/
00 6064

LST Active silver



matt black/
00 6071

LST Contrast gold



shiny petrol/
00 6072

LST Contrast silver



phantom/
fresh lemon/
00 6088

LST Contrast silver



silvermet/
lime/
00 6089

LST Active silver

lens technology:



package consists of:



RXready:






adivista S

a165

adapter parameters:

adapter model	lens horizontal	RX range	cylinder
a746	57 mm	-4.00/+2.00 dpt	-2.00/+2.00 dpt

Adapter Glazing a746



advanced edging parameters:

model / name	eye size	B measurement	bridge size	base curve
a165 / adivista S	66	41	10	8

model details

	58-59	60-62	63-66	67-70
single	-3.25/+1.25	-3.50/+1.50	-3.75/+1.75	-3.75/+1.75
progressive	-2.00/+1.00	-2.25/+1.00	-2.50/+1.25	-3.00/+1.50

PD

performance insert:



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis

model



a515



T-sight L a154



colors:

	frames	lenses
	black/ 00 6050	LST Contrast
	silver/ 00 6051	LST Contrast silver
	red/ 00 6054	LST Contrast silver
	matt copper/ 00 6060	LST Active silver
	matt titan/ 00 6061	LST Active silver

lens technology:



package consists of:



RXready:



T-sight L

a154

adapter parameters:

advanced edging parameters:

performance insert:



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis

model



a515



colors:

	frames	lenses
	matt black/grey/ 00 6050	LST Active silver
	matt silver/grey/ 00 6052	LST Contrast silver light
	matt black/grey/ 00 6054	LST Polarized
	matt silver/grey/ 00 6055	LST Polarized
	navy blue/ 00 6056	LST Contrast silver
	black/green/ 00 6060	LST Contrast gold
	white/red/ 00 6062	LST Active silver

lens technology:



package consists of:



RXready:



retego

a376

adapter parameters:

adapter model	lens horizontal	RX range	cylinder
a518	55 mm	-4.00/+4.00 dpt	-2.00/+2.00 dpt

Adapter Glazing a518



mm 55 x 40 (1929 mm²)



mm 62



mm 21



° 22

advanced edging parameters:

model / name	eye size	B measurement	bridge size	base curve
a376 / retego	61	42	15	8

model details

	58-59	60-62	63-66	67-70
single	-2.50/+1.25	-2.75/+1.50	-3.00/+1.50	-3.25/+1.75
progressive	-1.75/+0.75	-2.00/+1.00	-2.25/+1.25	-2.50/+1.50

PD

performance insert:



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis

model




a515



colors:

	frames	lenses
	shiny black/ 00 6050	LST Active silver
	shiny white/ 00 6051	LST Active silver
	shiny pink/ 00 6052	LST Active (antifog)
	shiny brown/ 00 6053	LST Contrast silver
	shiny black pol/ 00 6054	LST Polarized
	shiny white vario/ 00 6055	LST Vario
	red transparent/ 00 6056	LST Contrast silver
	blue transparent/ 00 6057	LST Active silver

lens technology:



package consists of:



RXready:



raylor L

a404

adapter parameters:

adapter model	lens horizontal	RX range	cylinder
a532	65 mm	-2.00/+ .50 dpt	-2.00/+2.00 dpt



Adapter Glazing a532



mm 58 x 42 (2005 mm²)



mm 65



mm 23



° 26

advanced edging parameters:

model / name	eye size	B measurement	DBL	base curve
a404 / raylor L	65	43.3	16	7.01-8.51

model details

		58-59	60-62	63-66	67-70
PLY/TRIVEX	S	-2.00/+ .75	-2.25/+1.00	-2.50/+1.00	-2.75/+1.25
PLY/TRIVEX	P	-1.00/+ .50	-1.25/+ .50	-1.50/+1.00	-1.75/+1.00

PD (S - Single Vision | P - Progressive)

performance insert:



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt




rimless insert chassis
model

a515



colors:

	frames	lenses
	shiny black/ 00 6050	LST Active silver
	shiny white/ 00 6051	LST Active silver
	shiny pink/ 00 6052	LST Active (antifog)
	shiny brown/ 00 6053	LST Contrast silver
	shiny black pol/ 00 6054	LST Polarized
	shiny white vario/ 00 6055	LST Vario
	red transparent/ 00 6056	LST Contrast silver
	blue transparent/ 00 6057	LST Active silver

lens technology:



package consists of:



RXready:



raylor S

a405

adapter parameters:

adapter model	lens horizontal	RX range	cylinder
a533	60 mm	-2.50/+0.75 dpt	-2.00/+2.00 dpt



Adapter Glazing a533



mm 52 x 38 (1668 mm²)



mm 59



mm 22



24°

advanced edging parameters:

model / name	eye size	B measurement	DBL	base curve
a405 /raylor S	60	39.9	15	7.01-8.51

model details

	58-59	60-62	63-66	67-70
PLY/TRIVEX S	-2.75/+1.00	-3.00/+1.25	-3.25/+1.50	-3.50/+1.75
PLY/TRIVEX P	-2.00/+0.75	-2.00/+1.00	-2.25/+1.25	-2.50/+1.50

PD (S - Single Vision | P - Progressive)

performance insert:



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt



rimless insert chassis
model





a515



Supernova™ pro L a176



colors:

	frames	lenses
	chrome/black/ 00 6050	LST Active silver
	white/red/ 00 6051	LST Bright (antifog)
	petrol/off-white/ 00 6052	LST Active (antifog)
	green/black/ 00 6053	LST Active (antifog)

lens technology:



package consists of:



RXready:



Supernova™ pro L

a176

adapter parameters:

advanced edging parameters:

performance insert:



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis

model







a515



Supernova™ pro S a177



colors:

	frames	lenses
	chrome/black/ 00 6050	LST Active silver
	white/red/ 00 6051	LST Bright antifog
	petrol/off-white/ 00 6052	LST Active antifog
	green/black/ 00 6053	LST Active antifog

lens technology:



package consists of:



RXready:



Supernova™ pro S

a177

adapter parameters:

advanced edging parameters:

performance insert:



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis

model



a515



Supernova™ a150



colors:

	frames	lenses
	black/ 00 6050	LST Active silver
	chrome/white/ 00 6066	LST Active silver
	phantom/ collegiate gold/ 00 6067	LST Active (antifog)
	shiny black/ pink/ 00 6073	LST Active silver light

lens technology:



package consists of:



RXready:



Supernova™

a150

adapter parameters:

advanced edging parameters:

performance insert:



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis

model



a515



adizero L a170



colors:

	frames	lenses
	shiny black/white/ 00 6050	LST Active (antifog)
	shiny aluminium/black/ 00 6051	LST Polarized
	matt black/black/ 00 6052	LST Active silver
	shiny transparent/ black/ 00 6053	LST Vario
	shiny black/ white/ 00 6054	LST Polarized
	shiny petrol/ neon green/ 00 6060	LST Contrast silver
	matt white/ neon green/ 00 6062	LST Active silver

lens technology:



package consists of:



RXready:



adizero L

a170

adapter parameters:

adapter model	lens horizontal	RX range	cylinder
a513	63 mm	-4.00/+2.00 dpt	-2.00/+2.00 dpt

Adapter Glazing a513



mm 63 x 38 (1968 mm²)



mm 67



mm 17



28

advanced edging parameters:

model / name	eye size	B measurement	bridge size	base curve
a170 / adizero L	72	41	10	8

model details

	58-59	60-62	63-66	67-70
single	-2.50/+1.00	-2.75/+1.00	-2.75/+1.25	-3.00/+1.25
progressive	-1.50/+0.50	-1.75/+0.50	-2.00/+0.75	-2.25/+1.00

PD

performance insert:



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis

model



a515



adizero S a171



colors:

	frames	lenses
	shiny black/white/ 00 6050	LST Active (antifog)
	shiny aluminium/black/ 00 6051	LST Polarized
	matt black/black/ 00 6052	LST Active silver
	shiny transparent/ black/ 00 6053	LST Vario
	shiny black/ white/ 00 6054	LST Polarized
	shiny petrol/ neon green/ 00 6060	LST Contrast silver
	matt white/ neon green/ 00 6062	LST Active silver

lens technology:



package consists of:



RXready:



adizero S

a171

adapter parameters:

adapter model	lens horizontal	RX range	cylinder
a514	57 mm	-4.00/+2.00 dpt	-2.00/+2.00 dpt

Adapter Glazing a514



mm 57 x 36 (1699 mm²)



mm 61



mm 17



28

advanced edging parameters:

model / name	eye size	B measurement	bridge size	base curve
a171 / adizero S	66	38	10	8

model details

	58-59	60-62	63-66	67-70
single	-3.00/+2.25	-3.25/+2.75	-3.50/+2.50	-3.75/+2.75
progressive	-2.25/+2.00	-2.75/+2.00	-3.25/+2.50	-3.50/+2.50

PD

performance insert:



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis

model



a515



adilibria halfrim L a385



colors:

	frames	lenses
	shiny black/grey/ 00 6050	LST Vario
	shiny brown/ chocolate/ 00 6051	LST Contrast
	shiny berry/ mauve/ 00 6052	LST Active (antifog)
	shiny khaki/grey/ 00 6053	LST Contrast silver light
	shiny black/ grey/ 00 6059	LST Polarized
	shiny khaki/grey/ 00 6060	LST Polarized
	ivory/white/ 00 6061	LST Bluefilter silver

lens technology:



package consists of:



RXready:



adilibria halfrim L

a385

adapter parameters:

adapter model	lens horizontal	RX range	cylinder
a517	59 mm	-4.00/+2.00 dpt	-2.00/+2.00 dpt

Adapter Glazing a517



mm

59 x 38 (1895 mm²)



mm

62



mm

21



°

25

advanced edging parameters:

model / name	eye size	B measurement	bridge size	base curve
a385 / adilibria halfrim L	70	40	15	8

model details

	58-59	60-62	63-66	67-70
single	-2.50/+0.75	-2.50/+0.75	-2.75/+1.00	-3.00/+1.25
progressive	-1.00/+0.75	-1.25/+0.75	-1.50/+1.00	-1.75/+1.00

PD

performance insert:



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis

model



a515



adilibria halfrim S a389



colors:

	frames	lenses
	shiny brown/ chocolate/ 00 6051	LST Contrast
	shiny berry/ mauve/ 00 6052	LST Active (antifog)
	black/ red/ 00 6067	LST Active silver
	magenta/ pink/ 00 6068	LST Contrast silver
	green/ black/ 00 6069	LST Active silver

lens technology:



package consists of:



RXready:



adilibria halfrim S

a389

adapter parameters:

adapter model	lens horizontal	RX range	cylinder
a519	54 mm	-4.00/+4.00 dpt	-2.00/+2.00 dpt

Adapter Glazing a519



mm 54 x 35 [1615 mm²]



mm 57



mm 20



25°

advanced edging parameters:

model / name	eye size	B measurement	bridge size	base curve
a389 / adilibria halfrim S	65	38	15	8

model details

	58-59	60-62	63-66	67-70
single	-2.50/+1.00	-2.50/+1.00	-2.75/+1.25	-3.00/+1.25
progressive	-1.50/+1.00	-1.50/+1.00	-1.75/+1.25	-1.75/+1.25

PD

performance insert:



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis

model



a515



adilibria halfrim II a390 L



colors:

	frames	lenses
	purple beauty/ 00 6051	LST Polarized
	black/red/ no floral print/ 00 6067	LST Active silver
	magenta/pink/ no floral print/ 00 6068	LST Contrast silver
	green/black/ no floral print/ 00 6069	LST Active silver

lens technology:



package consists of:



RXready:



adilibria halfrim II

a390 L

adapter parameters:

adapter model	lens horizontal	RX range	cylinder
a523	59 mm	-4.00/+2.00 dpt	-2.00/+2.00 dpt

Adapter Glazing a523



mm

59 x 36 [1832 mm²]



mm

61



mm

21



25°

advanced edging parameters:

performance insert:



model	lens horizontal	RX range	cylinder
a779	46 mm	-4.00/+4.00 dpt	-1.00/+1.00 dpt

rimless insert chassis

model



a515



mactelo
a379



colors:

	frames	lenses
	shiny black/ 00 6050	grey
	shiny white/ 00 6051	LST Active gold
	matt dark chocolate/ 00 6052	LST Contrast
	matt stone/ 00 6053	LST Contrast silver
	shiny black/ 00 6054	grey polarized
	matt dark chocolate/ 00 6055	LST Polarized
	matt black/ 00 6056	LST Contrast silver

lens technology:



package consists of:



RXready:



mactelo

a379

adapter parameters:

adapter model	lens horizontal	RX range	cylinder
a518	55 mm	-4.00/+4.00 dpt	-2.00/+2.00 dpt

Adapter Glazing a518



mm 55 x 40 (1929 mm²)



mm 62



mm 21



° 22

advanced edging parameters:

model / name	eye size	B measurement	bridge size	base curve
a379 / mactelo	61	42	15	8

model details

	58-59	60-62	63-66	67-70
single	-2.25/+1.00	-2.50/+1.25	-2.75/+1.25	-3.00/+1.50
progressive	-1.25/+0.75	-1.25/+0.75	-1.50/+0.75	-2.00/+0.75

PD

performance insert:



mactelo II a400



colors:

	frames	lenses
	shiny white/ 00 6051	LST Contrast
	taupe met/ 00 6052	LST Contrast gold
	shiny black/ 00 6058	LST Active silver

lens technology:



package consists of:



RXready:



mactelo II

a400

adapter parameters:

advanced edging parameters:

performance insert: